



**SPECIFICATIONS**

Current rating: 5 amps  
 Operating voltage: 250 VAC  
 Insulator material: PBT, glass reinforced, UL94V-0  
 Contact material: Phosphor bronze  
 Contact plating: Tin, gold or duplex  
 Contact resistance: 10 milliohms max.  
 Insulator resistance: 5,000 megohms min  
 Withstanding: 1,000 VAC RVNS Min  
 Operating temperature: -55° C to +125° C

P.C.Board Layout

Series	No. of Rows	Type	No. of Pins	Pin Length (Inches)	Plating
CCDPH	X	XX	XX	(A/B/E)	XX
Pin header, dual insulator 1.27mm pitch	2=Dual rows 1=Single row	Blank=Straight SM=Surface mount RA=Right Angle	1-40 (single row) 2-80 (double row)	See diagram for A,B and E Dimensions	GDXX=Gold    XX=Flash if blank, TN=Tin        03, 05, 10, 15, SGXX=Selective 30µ"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CCDPH-2-XX-XX-(A/B/E)-XX**

Description: Dual insulator pin header .050" x .050"