



SPECIFICATIONS

Current Rating: 3 Amp
 Voltage Rating: 500V for 1 Minute
 Insulation Resistance: 5000 Megohms min at 500 VDC
 Contact Resistance: 20 Milliohms Max
 Insulator: PBT +30% Glass Fiber UL94V-0
 Contact: Phosphor Bronze or Brass
 Plating: Gold over Nickel (std)
 Temperature Range: -40C to +105C

Circuit	Dimension					Circuit	Dimension				
	A	B	C	D	E		A	B	C	D	E
10	15.84	24.06	27.40	34.94	41.24	64	122.76	130.98	134.32	141.86	148.16
12	19.80	28.02	31.36	38.90	45.20	70	134.64	142.86	146.20	153.74	160.04
16	27.72	35.94	39.28	46.82	53.12	72	138.60	146.82	150.16	157.70	164.00
20	35.64	43.86	47.20	54.74	61.04	86	166.32	174.54	177.88	185.49	191.48
24	43.56	51.78	55.12	62.66	68.96						
26	47.52	55.74	59.08	66.62	72.92						
28	51.48	59.70	63.04	70.58	76.88						
30	55.44	63.66	67.00	74.54	80.84						
32	59.40	67.62	70.96	78.50	84.80						
36	67.32	75.54	78.88	86.42	92.72						
40	75.24	83.46	86.80	94.34	100.64						
44	83.16	91.38	94.72	102.26	108.56						
46	87.12	95.34	98.68	106.22	112.52						
50	95.04	103.26	106.60	114.14	120.44						
56	106.92	115.14	118.48	126.02	132.32						
60	114.84	123.06	126.40	133.94	140.24						
62	118.80	127.02	130.36	137.90	144.20						

Series	Type	Positions	Mounting	Contact Material	Plating	Options
CCE-B	KSL	XX	XX	XX	XX	XX
Card edge connector	3.96mm Pitch	10-86 Positions	ST=Straight RA=Right angle SD=Straddle tail	PB=Phosphor Bronze B=Brass	TN=Tin SGXX=Selective Gold GDXX=Gold XX;Flash if blank, 3,5,10µin	[blank]=No Mounting Ears MER=Mounting ears

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/11/07
				Checked	Lizzy	09/11/07
				Drawn	Tina	09/11/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CCE-B-KSL-XX-RA-XX-GD-XX**

Description: Card edge connector, 2.54mm x 5.08mm, vertical mount