



SPECIFICATIONS

Current Rating: 3 amp
 Contact Resistance: 20 miniohms max
 Operating Temp: -55°C to +105°C
 Voltage Rating: 800 VAC 1 min
 Insulation Resistance: 5000 megaohms min.
 Insertion Force: 412 grams max. per pair
 Withdrawal Force: 32 grams min. per pair
 Insulation: Glass-filled P.B.T. is 94V-0 rated
 Contact: Phosphor Bronze selective gold plating over nickel

Dimensions					
Contacts (S/D)	A	B	C	D	E
12/24	51.69	45.09	37.38	33.22	27.94
22/44	77.09	70.49	62.78	58.62	53.34
24/48	82.17	75.57	67.86	63.70	58.42
25/50	84.71	78.11	70.40	66.24	60.96
28/56	92.33	85.73	78.02	73.86	68.58
30/60	97.41	90.81	83.10	78.94	73.66
35/70	110.11	113.51	95.80	91.64	86.36
36/72	112.65	106.05	98.34	94.18	88.90
43/86	130.43	123.83	116.12	111.96	106.68
44/88	133.17	126.57	118.66	114.50	109.22

Series	Positions	Tail	Plating	Options
CCE	XXY	X	SG	XX
Card Edge Connector	See Table XX=Positions Y: S=Single Row D=Dual Row	A=4.7 mm B=6.1 mm C=14.1 mm D=21.8 mm	SG=Selective Gold	Blank=none EM=mounting ears

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/07/04
				Checked	Lizzy	08/07/04
				Drawn	Tina	08/07/04
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CCE-XX-X-SG-EM**

Description: 2.5 mm Card Edge Connector