

FPC/FPC Dimension  
Thickness 0.3±0.05mm

**SPECIFICATIONS**  
 Current Rating: 0.5 AMP  
 Contact Material: Phosphor Bronze  
 Contact Resistance: 30mΩ max. at DC 100mA  
 Housing Material: High Temp. Plastic UL94V-0  
 Insulation Resistance: 500MΩ min at DC 500V  
 Leg Material: Brass  
 Withstanding: AC 250V for 1 minute  
 Operating Temp: -55°C ~ +105°C

Series	Pitch	Type	Positions	Style	Plating	Packing
CCFC	100	2432	XX	X	TN	XX
FPC/FPC Non Zif	100=1.00mm	Type 2432	03-32	R=Right Angle V=Vertical SS=Side Entry Surface Mount	TN=Tin	Blank=Bulk TR=Tape & Reel TB=Tube


RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/15/06
				Checked	Lizzy	10/15/06
				Drawn	Tina	10/15/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CCFC-100-2432-XX-V-TN**

Description: FPC/FPC Type 2432 Non Zif Connector



UNIT: mm