



SPECIFICATIONS

Housing material:

PBT, UL94V-1

Positions:

4-80

Dimensions

Pos.	A	B	Pos.	A	B
4	5.08	2.54	42	53.34	50.80
6	7.62	5.08	44	55.88	53.34
8	10.16	7.62	46	58.42	55.88
10	12.70	10.16	48	60.96	58.42
12	15.24	12.70	50	63.50	60.96
14	17.78	15.24	52	66.04	63.50
16	20.32	17.78	54	68.58	66.04
18	22.86	20.32	56	71.12	68.58
20	25.40	22.86	58	73.66	71.12
22	27.94	25.40	60	76.20	73.66
24	30.48	27.94	62	78.74	76.20
26	33.02	30.48	64	81.28	78.74
28	35.56	33.02	66	83.82	81.28
30	38.10	35.56	68	86.36	83.82
32	40.64	38.10	70	88.90	86.36
34	43.18	40.64	72	91.44	88.90
36	45.72	43.18	74	93.98	91.44
38	48.26	45.72	76	96.52	93.98
40	50.80	48.26	78	99.06	96.52
			80	101.60	99.06

Series	Rows	Positions	Options
CCHA	XX	XX	XX
Housing (Dupont) .100" Pitch	01=Single 02=Dual	01-40 Single Row 04-80 Dual Row	Blank=None PA=1.42 Center Polarized (Dual Row only) PB=2.85mm Center Polarized (dual row only)

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CCHA-02-XX-X**

Description: Housing, 2.54mm (.100") pitch, dual row