



SPECIFICATIONS

Current rating: 7 amps
 Voltage rating: 250 V
 Pin; Brass
 Pin plating: Tin
 Insulator: Phenolic bakelite, UL 94V-0
 Insulation resistance: 1000 megohms min.
 Withstanding: 0500 VAC/minute
 Operating temp.: -25°C to +95°C

NOTES:

Pin (round) 2.36
 PCB thickness 1.6
 PCB hole diameter: 2.55

Dimensions		
Pos.	L	L1
1	6.50	
2	18.00	
3	26.00	8.00
4	34.00	16.00
5	42.00	24.00
6	50.00	32.00

Dimensions	
H	16.50
H1	10.50
P	8.00
P1	10.00
T	1.60
W	6.50

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CCPH-A10201-X**

Description: Pin header