



SPECIFICATIONS

Operating Current: 3A
 Operating Voltage: 200V
 Contact Resistance: ≤8mΩ
 Mechanical Life: 500
 Operating Temperature: -55°C~+105°C
 Relative Humidity: 40+2°C reach (92~98)%
 Working Pressure: 101.33KPa~4kPa
 Vibration: 10~2000Hz, 196m/s²
 Collision: 10~40 Secondary/min 392m/s²

Work Environment	Withstanding	Insulation Resistance
Normal	1000V	≥1000MΩ
High Temperature	700V	≥500MΩ
Damp	500V	≥50MΩ
Low Pressure	200V	-

Series	Type	Style	Positions	Panel Side	Shell Side
CCTC	PC4	KP30	XX	X	X
Circular Connector	PC4 Connector	PC4 with Shell & Mounting Flange	04,07,10,19,32,50	T=Receptacle Male Contacts Rectangular Flange	Z=Plug Female Contacts

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/05/11
				Checked	Lizzy	03/05/11
				Drawn	Tina	03/05/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CCTC-PC4-KP30-XX-X-X**

Description: PC4 Circular Connector Set