



SPECIFICATIONS

Contact Resistance: 20m OHM MAX.
 Insulation Resistance: 100M OHM AT 500V D.C.
 Withstanding: AC 500V 1 Min
 Insertion Force: 5.0 KG Max.
 Withdrawal Force: 1-3.5 KG
 Life Test: 5,000 Cycles Min. after testing, contact resistance shall not exceed 100m OHM
 Current Rating: AC: 100V 2A

Item	Name	Material	Finish
1	Body	P.B.T.	
2	Earth Terminal	BSR-H 0.2t	Nickel Plated
3	Plate	Bakelite	PL-PEM 1.4t
4	Contact Terminal	BSR-0.5H 0.7t	TIN

Series	Positions	Housing	Ground Tab Spacing	Options
CDJB	XX	X	X	X
Circular DIN jack	05=5 positions (3-9 available)	A=Non-shielded B=Metal shield	1=10mm 2=5mm	[blank]=None L=Lock GS=Ground spring

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/05/98
				Checked	Lizzy	11/05/98
				Drawn	Tina	11/05/98
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CDJB-05-B-2**

Description: 5 Pin - 180 din connector