



**MOUNTING HOLE  
(TOP VIEW)**

**SPECIFICATIONS**

- Contact Resistance: 20m OHM MAX.
- Insulation Resistance: 100M OHM AT 500V D.C.
- Withstanding: AC 500V 1 Min
- Insertion Force: 5.0 KG Max.
- Withdrawal Force: 1-3.5 KG
- Life Test: 5,000 Cycles Min. after testing, contact resistance shall not exceed 100m OHM
- Current Rating: AC: 100V 2A  
DC: 24V 1A

Item	Name	Material	Finish
1	Body	P.B.T.	UL94V-0
2	Earth Terminal	PBSR-0.2t	Tin
3	Cover	PBT	UL94V-0
4	Contact	BSR-H/2 0.7t	Tin

Series	Positions	Housing	Ground Tab Spacing	Options
CDJB	XX	X	X	X
Circular DIN jack	05=5 positions (3-9 available)	A=Non-shielded B=Metal shield	1=10mm 2=5mm	[blank]=None L=Lock GS=Ground spring

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/05/98
				Checked	Lizzy	11/05/98
				Drawn	Tina	11/05/98
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CDJB-07-A-2**

Description: 7 Pin - 180 din connector