



PCB LAYOUT

**SPECIFICATIONS**

Contact Resistance: 20m OHM  
 Insulation Resistance: DC 500V 100M OHM Min.  
 Voltage Withstanding: AC 500V 1 Minute  
 Insertion Force: 6.5KG Max.  
 Withdrawal Force: 1-5 KG  
 Durability: 5000 Cycles Min. after Testing  
 Current Rating: AC 100V 2A, DC 24V 1A

Item	Name	Material	Remarks
1	Body	PBT	UL94V-0
2	Cover	PBT	UL94V-0
3	Earth Terminal	PBSR 0.25t	Tin Plating
4	Contact Terminal	BSR-H/2.07t	Tin Plating

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/25/05
				Checked	Lizzy	08/25/05
				Drawn	Tina	08/25/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: in	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CDJB-801-08-A-M**

Description: 8 Pin DIN Socket, 262°