



SPECIFICATIONS

Contact material: Brass
 Insulator material: PBT, glass reinforced UL94V-0 rated
 Contact plating: Gold flash plated over nickel

| Series | No. of Rows | Type | No. of Pins | Pin Length (Inches) | Plating |
|---|-----------------------------|--|--|--------------------------------------|---|
| CDPH | X | XX | XX | (A/B/E) | XX |
| Pin header, dual insulator 2.54mm pitch | 2=Dual rows 1=Single row | Blank=Straight SM=Surface mount RA=Right Angle | 1-40 (single row) 2-80 (double row) | See diagram for A,B and E Dimensions | GDXX=Gold XX=Flash if blank, TN=Tin 03, 05, 10, 15, SGXX=Selective 30μ" |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|--|--------|----------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | | | 0.0 ± 0.35 0.00 ± 0.20 Angles ± 3' | | |
| | | | | UNIT: mm | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CDPH-1-ST-XX-CS(A/B/C)-XX**

Description: 2.54mm pin header, dual insulator, straight type