



**SPECIFICATIONS**

Contact material: Brass  
 Insulator material: PBT, glass reinforced UL94V-0 rated  
 Contact plating: Gold flash plated over nickel

Series	No. of Rows	Type	No. of Pins	Pin Length (Inches)	Plating
CDPH	X	XX	XX	(A/B/E)	XX
Pin header, dual insulator 2.54mm pitch	2=Dual rows 1=Single row	Blank=Straight SM=Surface mount RA=Right Angle	1-40 (single row) 2-80 (double row)	See diagram for A,B and E Dimensions	GDXX=Gold    XX=Flash if blank, TN=Tin        03, 05, 10, 15, SGXX=Selective 30μ"

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CDPH-1-ST-XX-CS(A/B/E)-XX**

Description: 2.54mm pin header, dual insulator, straight type