



SPECIFICATIONS

Current Rating: 1.5 Amp Min.
 Contact Material: Brass, Gold over Nickel plating
 Tin Plating on Solder Area
 Contact Resistance: 20 Milliohms Max.
 Body Material: Nylon UL94V-0, White
 Latch Material: Nylon UL94V-0, White
 Harpoon Material: Brass, Tin Plating over Nickel
 Shell Material: SPCC, Nickel Plating
 Shell Resistance: 50 Milliohms Max
 Insulation Resistance: 1000 Megohms Min.
 Mating Force: 4.5 KG Max. at 25 mm/minute
 Unmating Force: 1.0 KG Min. & 4.0 KG Max. at 25 mm/minute
 Durability: 100 Mating Cycles
 Withstanding: 500 V DC
 Operating Temp: -20°C to +85°C

Series	Type	Material	Options	Jack Screw	Finish
CDVI	RAXX	BNW	XX	XX	XX
DVI Connector	XX: 24=24pos (digital) 29=29pos (analog)	Brass Contacts Nylon 66, White	Blank=None CP=Centering Post BL=Board Locks	Blank=None JS=Jack Screw	GD=Gold finish GD15=15u" Gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/12/07
				Checked	Lizzy	03/12/07
				Drawn	Tina	03/12/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CDVI-RA29-BNW-P-XX-XX**

Description: DVI 029 Pin Connector