

- All mounting types available with boardlocks (BL)
- Straight (A mount) type available in press fit (PF)
- All types available with first mate last break (FMLB)


Series	Gender	Mounting	Contacts	Tail Length	Pitch	Loaded Rows	Plating	Type	Options
CED	X	X	XXX	XX	XX	X	SGX	R	XX
DIN41612	1-A=Male straight 2-B=Female right angle 1-B=Male right angle 2-A=Female straight		B1: 96, 64, 32 B2: 48, 32, 16	A1=2.9mm A2=2.5mm A1()=Custom	B1=2.54mm B2=5.08mm	1=A 5=A, C (C only) 2=B 6=B, C (C only) 3=C (C only) 7=A, B, C 4=A, B	SG=Selective gold 1=30µ" (Level 1) 2=10-20µ" (Level 2) 3=Flash (Level 3)	R type (See also C, B, Q)	[Blank]=None PF=Press fit BL=Boardlocks HT=High temp. material

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/12/03
				Checked	Lizzy	02/12/03
				Drawn	Tina	02/12/03
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-1-A-XX-A1(X)-B1-X-SGX-R-PF**

Description: DIN41612 connector, R type, 96 pins



UNIT: mm