

Pitch	Position	Rows with contacts
2.54mm	96	a b c
	64	a b -
	64	a - c
5.08mm	32	a - -
	48	a b c
	32	a b -
	32	a - c
16	a - -	

SPECIFICATIONS

- Current rating: 2 amps
- Contact material: Brass
- Contact resistance: 30 milliohms max. at 100 milliamps DC
- Housing material: PBT, 30% glass filled, UL94V-0
- Insulation resistance: 1,000 megohms min. at 500VDC
- Withstanding: 1,000VAC for 1 min.
- Operating temperature: -55°C to +105°C

- All mounting types available with boardlocks (BL)
- Straight (A mount) type available in press fit (PF)
- All types available with first mate last break (FMLB)

UNIT: INCH
MM

Series	Gender	Mounting	Contacts	Pin Length	Pitch	Loaded Rows	Plating	Type	Options
CED	X	X	XX	XX	XX	X	SGX	C	XX
DIN41612	1-B=Male right angle 2-A=Female straight		16, 32, 48, 64, 96 (see chart)	A1=2.9mm	B1=2.54mm B2=5.08mm	1=A 5=A & C 2=B 7=A, B & C 4=A & B	SGX=Selective gold 1=30µ" (Level 1) 2=10-20µ" (Level 2) 3=Flash (Level 3)	C=C type (See also B, Q & R)	[Blank]=None PF=Press fit BL=Boardlocks HT=High temp. material



RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-1-B-XX-A1-XX-X-SGX-C-XX**

Description: DIN 41612, C type, male



Angles ± 3'

UNIT: mm