


(13.8)
TERMINATED
HEIGHT



SPECIFICATIONS

Current Rating: 1 Amp
 Contact Material: Phosphor Bronze
 Contact Resistance: 30mΩ max.
 Insulation Material: PBT, glass reinforced, UL94V-0
 Withstanding: 500V AC for 1 minute
 Operating Temp: -40°C to +105°C

Dimensions				
Pos.	A	B	C	D
32(A+C)	55	44.8	38.10	50
64(A+C)	95	85.4	78.74	90

Series	Gender	Mounting	Contacts	Pitch	Loaded Rows	Plating	Type
CED	1	C	XX	B1	X	SGX	XX
DIN41612	1-C=Male IDC		32,64	B1=2.54 Pitch (for 1.27mm Flat Cable)	4=A+B 5=A+C	SG=Selective Gold 1=30u" (level 1) 2=10-20u" (level 2) 3=Flash (level 3)	C (96 positions) C2 (48 positions)



RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/15/06
				Checked	Lizzy	10/15/06
				Drawn	Tina	10/15/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-1-C-32-B1-5-SG3-C2**

Description: DIN41612 I.D.C. Type, 3 Rows Male



Angles ± 3'

UNIT: mm