



RoHS compliant

Pitch	Position	Rows with contacts
2.54mm	32	a b
	16	a
5.08mm	16	a b
	8	a

SPECIFICATIONS

Current rating: 2 amps
 Contact material: Brass
 Contact resistance: 30 milliohms max. at 100 milliamps DC
 Housing material: PBT, 30% glass filled, UL94V-0
 Insulation resistance: 1,000 megohms min. at 500VDC
 Withstanding: 1,000VAC for 1 min.
 Operating temperature: -55°C to +105°C

- All mounting types available with boardlocks (BL)
- Straight (A mount) type available in press fit (PF)
- All types available with first mate last break (FMLB)

Series	Gender	Mounting	Contacts	Pin Length	Pitch	Loaded Rows	Plating	Type	Options
CED	X	X	XX	XX	XX	X	SGX	B2	XX
DIN41612	1-B=Male right angle 2-A=Female straight		16, 32, 64 (see chart)	A1=4.0mm (PF=4.6mm) A2=2.5mm (PF=6.3mm) A3=13mm (PF=13mm) (str only) A4=17mm (PF=17mm) (str only)	B1=2.54mm B2=5.08mm	1=A 2=B 4=A & B	SG=Selective gold 1=30μ" (Level 1) 2=10-20μ" (Level 2) 3=Flash (Level 3)	B2 type (See also B, Q & R)	[Blank]=None PF=Press fit BL=Boardlocks HT=High temp. material

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99

0.0 ± 0.35 0.00 ± 0.20 Angles ± 3'

UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-2-A-XX-XX-XX-X-SGX-B2-PF**

Description: DIN 41612, B2 type, female, press fit, 2 rows