

SPECIFICATIONS

Current rating: 2 amps
 Contact Material: Phosphor Bronze
 Contact Resistance: 20 m ohms max
 Insulator Material: Polyester, UI94V-0
 Standard=Nylon-6T
 Insulator Resistance: 1000 Megohms min
 Finish: Tin, Gold Plated
 Standard=Gold flash all over
 Max Processing Temp: 230°C for 60 sec.
 260°C for 10 sec.
 Withstanding: AC 500V
 Operating Temp: -40°C ~ +85°C

RoHS compliant


Series	Type	Positions	Profile	Tail Length	Options
CED	PC104	120	X	X	XX
PCB socket	Type=PC104	120=120 positions	A=6.30 B=9.30	L=2.4mm (A only) M=2.8mm (B only) N=12.1mm (B only) CS=Custom	Blank=Solder tail PF=Pres Fit

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/05/06
				Checked	Lizzy	10/05/06
				Drawn	Tina	10/05/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-PC104-120-B-N**

Description: PC104 2.0mm Socket



UNIT: mm