



SPECIFICATIONS

Housing: High Temperature Plastic UL94V-0
 Contacts: Copper Alloy
 Insertion Depth: 4.0mm
 Current Rating: 2 Amp
 Withstanding: 500V AC/DC
 Insulation Resistance: 1000MΩ min.
 Contact Resistance: 20mΩ max.
 Operating Temp: -40°C to +105°C

| Series | Type | Positions | Profile | Tail Length | Options |
|------------|------------|-------------------|-------------------|---|----------------------------------|
| CED | PC104 | 120 | X | X | XX |
| PCB socket | Type=PC104 | 120=120 positions | A=6.30 BE=9.35 | L=2.4mm (A only) M=2.28mm (B only) N=12.1mm (B only) CS=Custom | Blank=Solder tail PF=Pres Fit |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|----------------|-----------------|-----------------|
| | | | | Approved | Howard | 10/05/06 |
| | | | | Checked | Lizzy | 10/05/06 |
| | | | | Drawn | Tina | 10/05/06 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles $\pm 3'$ |
| | | | | UNIT: mm | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-PC104-120-BE-M**

Description: .20mm PCB socket