



SPECIFICATIONS

Current rating: 2 amps
 Contact material: Copper Alloy
 Housing material: High Temp Plastic, UL94V-0
 Withstanding: 1,000VAC 1 min.
 Contact resistance: 30 mΩ max.
 Insulation resistance: 1000 MΩ min. at 500VDC
 Operating temperature: -25°C to +85°C

Series	Type	Positions	Profile	Tail Length	Options
CED	PC104	120	X	X	XX
PCB socket	Type=PC104	120=120 positions	A=6.30 B=9.35	L=2.4mm (A only) M=2.8mm (B only) N=12.1mm (B only) P=4.0mm (PF only) CS=Custom	Blank=Solder tail PF=Pres Fit

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/05/06
				Checked	Lizzy	10/05/06
				Drawn	Tina	10/05/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-PC104-120-X-X-PF**

Description: .20mm PCB socket