



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)

- SPECIFICATIONS**
- Current Rating: 1.5 Amp
 - Contact material: Phosphor Bronze
 - Contact Plating: Au or Sn over Ni
 - Insulator Material: PA9T+30%GF UL94V-0
 - Contact Resistance: 20m Ω Max.
 - Withstanding Voltage: 500V AC/DC
 - Insulation Resistance: 1000M Ω Min
 - Operating Temp: -40C to +105C

Series	Type	Positions	Profile	Tail Length	Options
CED	PC104	XXX	X	M	XX
PCB socket	Type=PC104	008-160 positions	A=6.30 B=9.35	M=3.00mm	Blank=Solder tail PF=Pres Fit

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/05/06
				Checked	Lizzy	10/05/06
				Drawn	Tina	10/05/06
				0.0 ± 0.35	0.00 ± 0.20	Angles $\pm 3'$
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-PC104-XXX-B-M-PF**

Description: 2.0mm PCB socket, PC104 Pressfit (Compliant Pin)