



RoHS compliant

Series	Type	Positions	Profile	Tail Length	Plating	Options
CED	PC104	XXX	X	M	XX	XX
PCB socket	Type=PC104	008-160 positions	A=6.30 B=9.35	M=3.00mm	TN=Tin SGXX=Selective Gold GDXX=Gold XX=Flash if blank, 10,15,30u"	Blank=Solder tail PF=Pres Fit

**SPECIFICATIONS**  
 Current Rating: 2.0 Amp  
 Contact material: Phosphor Bronze  
 Contact Plating: Au or Sn over Ni  
 Insulator Material: PA9T+30%GF UL94V-0  
 Contact Resistance: 20mΩ Max.  
 Withstanding Voltage: 500V AC/DC  
 Insulation Resistance: 1000MΩ Min  
 Operating Temp: -40C to +105C

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/10/13
				Checked	Lizzy	04/10/13
				Drawn	Tina	04/10/13
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CED-PC104-XXX-B-XX-M**

Description: 2.0mm PCB socket, PC104, Solder Contact