



SPECIFICATIONS

Current Rating: 0.5 Amp
 Contact Resistance: 30m Ohm Max.
 Insulator Resistance: 1000M ohm min.
 Insulator: PBT Glass Fiber UL94V-0, Black
 Contact Material: Phosphor Bronze
 Contact Plating: See Table
 Operating Temp: -40C ~ +105C

Dimensions			
Pos	A	B	C
06	8.01	2.54	2.54
08	9.28	3.81	3.81
10	10.55	5.08	5.08
12	11.82	6.35	6.35
14	13.09	7.62	7.62
16	14.36	8.89	8.89
20	16.90	11.43	11.43
22	18.17	12.70	12.70
26	20.71	15.24	15.24
30	23.25	17.78	17.78
34	25.79	20.32	20.32
36	27.06	21.59	21.59
40	29.60	24.13	24.13
44	32.14	26.67	26.67
50	35.95	30.48	30.48
60	42.30	36.83	36.83
68	47.38	41.91	41.91
80	55.00	49.53	49.53

Series	Positions	Polarized	Finish
CFC-C	XX	P	XX
.050"x.050" Flat Cable Socket	06-80 See Chart	P=Polarized	GDYY=Gold YY=Flash if blank, 03,05,10,15,20,3u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/24/05
				Checked	Lizzy	03/24/05
				Drawn	Tina	03/24/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFC-C-XX-P-XX**

Description: IDC Socket