



SPECIFICATIONS

ST Adapter Body: Zinc Alloy Die Casting w/ Nickel Plating
 Retainer: Zinc Alloy Die Casting with Nickel Plating
 Sleeve: Phosphor Bronze, Zirconia
 Dust Cap: Engineering Plastic (PVC)
 Washer: Steel with Nickel Plating
 Nut: Brass with Nickel Plating

SINGLE MODE (SM)
 Insertion Loss: 0.15/0.3 Typ/Max
 I.L. (dB) 500 Matings: 0.1
 Temp Range: -40C to +85C
 Retention Force: 300-600

MULTI MODE (MM)
 Insertion Loss: 0.2/0. Typ/Max
 I.L. (dB) 500 Matings: 0.1
 Temp Range: -40C to +85C
 Retention Force: 200-600

Series	Type	Body	Sleeve	Mode	Cap
CFO	002	X	X	X	XX
Fiber Optic Connectors	Panel Mount Coupler Type 002	M=Metal E=Engineering Plastic	P=Phos. Bronze Z=Zirconiam	SM=Single Mode MM=Multi Mode	RD=Red BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/08
				Checked	Lizzy	08/10/08
				Drawn	Tina	08/10/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFO-002-X-X-XX-XX**

Description: Fiber Optic Coupler