



SPECIFICATIONS

Housing Material: Copper-Nickel
 Alignment Sleeve: ZrO2
 Insertion Loss: 0.2dB MAX
 Durability: 0.15 dB MAX Increase
 Retention Force: 200~600 Grams
 Operating Temp: -40°C~+80°C

Item	Name	Material
1	ST Adaptor Cap	PVC
2	3/8"-24 UNEF Nut	Steel-Nickel
3	Washer	Steel-Nickel
4	FC-ST D-Type Body Key=2.2mm	Copper-Nickel
5	Sleeve	Ceramic
6	FC Adaptor Bush	Copper-Nickel
7	FC Adaptor Cap	PVC

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/29/07
				Checked	Lizzy	08/29/07
				Drawn	Tina	08/29/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFO-FC/STH-D**

Description: Fiber Optic Adaptor, Type FC to ST with Nut on ST