



SPECIFICATIONS
 Current Rating: 1 AMP
 Contact Resistance: 20mΩ max. at DX 100mA
 Housing Material: 30% Glass Filled PBT UL94V-0
 Insulator Resistance: 1000MΩ min. ad DC 500V
 Withstanding: AC 1000V for 1 minute
 Operating Temp: -55°C ~ +105°C

FFC/FPC Dimension
 Thickness 0.3±0.05mm

RoHS compliant

Series	Pitch	Type	Contacts	Style	Plating	Options
CFPC	100	2032	XX	X	TN	XX
FPC Connector	100=.100"	Type 2032	02-26	R=Right Angle V=Vertical	TN=Tin	[blank]=None TR=Tape & reel TB=Tube

Rev.	Description	Date	Approved	Drawing	Name	Date
A	PNT	08/28/14	GL	Approved	Howard	04/17/06
				Checked	Lizzy	04/17/06
				Drawn	Tina	04/17/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFPC-100-2032-XX-X-TN-XX**

Description: FFC/FPC Connector .100" (2.54mm)