



SPECIFICATIONS
 Current Rating: 1 A AC(rms)/DC
 Voltage Rating: 125 V AC(rms)/DC
 Terminal Material: Phosphor Bronze
 Plating Material: Tin Plated
 Contact Resistance: 20mΩ max
 Housing Material: Nylon UL94V-0
 Insulation Resistance: 100 MΩ min.
 Actuator Material: Nylon UL94V-0
 Fitting Nail: Phosphor Bronze
 Withstanding: 500 V AC/rms
 Operating Temp: -20°C ~ +85°C

RoHS compliant

Dimensions (mm)																							
Pos.	A	B	C	Pos.	A	B	C	Pos.	A	B	C	Pos.	A	B	C	Pos.	A	B	C	Pos.	A	B	C
3	2.0	8.6	4.4	10	9.0	15.6	11.4	17	16.0	22.6	18.4	24	23.0	29.6	25.4	31	30.0	36.6	32.4	38	37.0	43.6	39.4
4	3.0	9.6	5.4	11	10.0	16.6	12.4	18	17.0	23.6	19.4	25	24.0	30.6	26.4	32	31.0	37.6	33.4	39	38.0	44.6	40.4
5	4.0	10.6	6.4	12	11.0	17.6	13.4	19	18.0	24.6	20.4	26	25.0	31.6	27.4	33	32.0	38.6	34.4	40	39.0	45.6	41.4
6	5.0	11.6	7.4	13	12.0	18.6	14.4	20	19.0	25.6	21.4	27	26.0	32.6	28.4	34	33.0	39.6	35.4				
7	6.0	12.6	8.4	14	13.0	19.6	15.4	21	20.0	26.6	22.4	28	27.0	33.6	29.4	35	34.0	40.6	36.4				
8	7.0	13.6	9.4	15	14.0	20.6	16.4	22	21.0	27.6	23.4	29	28.0	34.6	30.4	36	35.0	41.6	37.4				
9	8.0	14.6	10.4	16	15.0	21.6	17.4	23	22.0	28.6	24.4	30	29.0	35.6	31.4	37	36.0	42.6	38.4				

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/02/08
				Checked	Lizzy	09/02/08
				Drawn	Tina	09/02/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFPC-100-85202-XX-RB-TN-XX**

Description: 1.0mm Pitch FCC/FPC Connector