



Dimensions				
Contacts	A	B	C	D
4	8.5	3	10	5.1
5	9.5	4	11	6.1
6	10.5	5	12	7.1
7	11.5	6	13	8.1
8	12.5	7	14	9.1
9	13.5	8	15	10.1
10	14.5	9	16	11.1
11	15.5	10	17	12.1
12	16.5	11	18	13.1
13	17.5	12	19	14.1
14	18.5	13	20	15.1
15	19.5	14	21	16.1
16	20.5	15	22	17.1
17	21.5	16	23	18.1
18	22.5	17	24	19.1
19	23.5	18	25	20.1
20	24.5	19	26	21.1
21	25.5	20	27	22.1
22	26.5	21	28	23.1
23	27.5	22	29	24.1
24	28.5	23	30	25.1

SPECIFICATIONS

- Housing: Thermoplastic
- Slider: Thermoplastic
- Contacts: Copper
- Voltage: 50V
- Current: 0.5A
- Operating Temp: -55C ~ +85C

Series	Pitch	Type	Contacts	Style	Plating	Options
CFPC	XXX	S113	XX	XX	XX	XX
FPC Connector	050=0.50mm 030=0.30mm 100=1.00mm 125=1.25mm	S113 ZIF Type S113H=Halogen Free	4-24 see chart	R=Right Angle V=Vertical VR=Vertical Reverse Pins U=Upper Contacts B=Bottom Contacts	TN=Tin over nickel GD=Gold Flash over nickel GD3=Gold 3u" over nickel	[blank]=None TR=Tape & Reel TB=Tube

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFPC-100-S113-XX-V-XX-XX**

Description: 1.0mm Pitch FPC/FFC Connector