





SPECIFICATIONS

Current rating: 1 amp
 Contact material: Phosphor bronze
 Contact plating: Tin
 Contact resistance: 20 milliohms max. at 100 mA DC
 Housing material: PBT 30% glass fill, UL 94V-0
 Insulator resistance: 5,000 megohm min. at 500 VDC
 Operating temperature: -55°C to +105°C




Top Entry Type




Side Entry Type

Dimensions	
A	(No. pos. X 2.54) + 5.48
B	(No. pos. X 2.54) + 3.35
C	(No. pos. -1) X 2.54



FFC/FPC Dimension
 Thickness 0.3± 0.05mm



P.C. Board Layout

Series	Positions	Style	Plating
CFPCC	XX	XX	TN
.100" FFC/FPC	6-27	ST=Straight RA=Right angle	TN=Tin

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFPCC-XX-XX-TN**

Description: .100" FFC/FPC connector, non ZIF type