



**SPECIFICATIONS**

- Contact Resistance: 30m Ohm Max.
- Insulation Resistance: 100M Ohm Min.
- Voltage: 40V Max.
- Current: 1.5A Max.
- Withstanding: 500V AC for 1 Minute
- Durability: 1500 Cycles
- Unmating Force: 9.8 Newton TO 39.2 Newton Max

Item	Name	Material	Remark
1	Contact	C2680	T=0.20mm Gold/Tin Plated
2	Housing	PA6T	94V-0 Nature/Black/White
3	Front Shell	C2680	T=0.40mm Nickel Plated
4	Back Shell	C2680	T=0.35mm Nickel Plated

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	01/04/10
				Checked	Lizzy	01/04/10
				Drawn	Tina	01/04/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CFW-A-1394-F-HB**

Description: IEEE 1394 A Type Socket