



Positions				
Contacts	A±0.20	B±0.20	C±0.20	D±0.20
16	14.22	12.45	10.10	7.62
20	17.78	16.00		
22	19.56	17.78		
24	21.34	19.56		
24	21.34	19.56	12.65	10.16
28	24.89	23.11		
30	26.67	24.89		
32	28.45	26.67		
40	35.56	33.78	17.70	15.24
42	37.34	35.56		
48	42.67	40.89		
52	46.23	44.45		
54	48.01	46.23		
56	49.78	48.01		
58	51.56	49.78		
60	53.34	51.56		
62	55.12	53.34	21.55	19.05
64	56.90	55.12		
64	56.90	55.12		

**SPECIFICATIONS**  
 Current Rating: 1A  
 Contact Material: Phosphor Bronze, 0.17mm thickness  
 Contact Resistance: 30 milliohms max  
 Contact Plating: Tin  
 Insulation Material: PBT, UL94V-0  
 Insertion Force: 45g max  
 Withdrawal Force: 14.5g min per contact  
 Capacitance: 0.5 picofarad max  
 Withstanding: 1000V RMS/minute  
 Operating Temp: -55°C to 105°C

Series	Positions	Plating
CICX-A	XX	TN
.07" Contact Spacing	See Chart	TN=Tin
X=row spacing		
3=.300" (7.6mm)		
4=.400" (10.16mm)		
6=.600" (15.24mm)		
75=.750" (19.05mm)		

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/01/06
				Checked	Lizzy	11/01/06
				Drawn	Tina	11/01/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CICX-A-XX-TN**

Description: .070 (1.78mm) Pitch IC Socket

G

G