



SPECIFICATIONS

Contact:	Phosphor Bronze
Plating:	Tin Plated
Insulator:	Glass Filled Thermoplastic Polyester UL94V-0
Current Rating:	1Amps/contact max.
Contact Resistance:	≤20mΩ/contact
Insulation Resistance:	≥1000MΩ at V=100V
Voltage Rating:	250 VAC/DC
Operating Temp:	Gold Plated -55C to +105C Tin Plated -40C to +105C

Series	Pitch	Positions	Type	Dip Length	Plating
CIS	X	XX	XX	X	XX
Single Row Socket	A=1.00" (2.54mm)	02-24	ST=Straight	A=3.2	TN=Tin

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/12/10
				Checked	Lizzy	08/12/10
				Drawn	Tina	08/12/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CIS-A-XX-ST-A-TN**

Description: 2.54mm Pitch IC Sockets Single Row DIP Length 3.20mm