




**SPECIFICATIONS**

- 1. Housing material: ABS+PC, UL94V-0, black
  - 2. Insert material: Polycarbonate, UL94-HB, transparent
  - 3. Shield material: Bronze, nickel plated
  - 4. Contact material: Phosphor bronze  
50-60µ" nickel plate  
3mm 50µ" gold plate in contact area  
900g/8 contacts
- Insertion force: 7.7kg jack to plug  
Retention strength: -40°C to +80°C  
Operating temp.: 750 cycles plug-jack mating-unmating  
Durability:



Note: CAT 6 performance complies with ANSI/TIA/EIA B.2-1 standards.

Series	Positions	Contacts	Color	Plating	Type	Options
CLC	8	08	BK	XX	S6	PM
Modular inline coupler keystone jack	8=8 positions	08=8 contacts	BK=Black	P1=15µ" gold P2=30µ" gold P3=50µ" gold	S6=CAT 6 shielded	[blank]=None PM=Panel mount

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/26/07
				Checked	Lizzy	02/26/07
				Drawn	Tina	02/26/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
440 Lincoln Blvd., Middlesex, New Jersey 08846  
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CLC-8-08-BK-XX-S6-PM**

Description: Inline modular coupler keystone jack, 8P8C, shielded, CAT 6