



SPECIFICATIONS

Pin Sleeve: Brass
 Clip Contact: Beryllium Copper
 Body: Polyamide Glass filled UL94V-0
 Current Rating: 3 Amps
 Contact Resistance: 4mΩ
 Insulation Resistance: 1000MΩ
 Voltage Rating: 60 VAC
 Insertion Force: <250g
 Withdrawal Force: >50g
 Mechanical Life: min 200
 Operating Temp: -55C to +125C

Dimensions					
Contact	A	B	Contact	A	B
06	7.62	5.08	18	22.86	20.32
08	10.16	7.62	20	25.40	22.86
10	12.70	10.16	24	30.48	27.94
14	17.78	15.24	28	35.56	33.02
16	20.32	17.78			

Series	Positions	Plating	Frame	Options
CMCX	XX	XX	XXX	WWTX
Machine Contact	3: 06, 08, 10, 14, 16, 18, 20, 22, 24, 28	TN=Tin	Blank=Std open with bars	Wire Wrap Pin Length
Socket	4: 20, 22, 24, 28, 32	SGXX=Selective	OPN=Open	X: 1=11.58
X=3,4,6 " Row	6: 24, 28, 32, 26, 40, 42,	GDXX=Gold	CLD=Closed	2=14.12
Space	48, 50, 52	XX=Flash if blank, 10,30u"		3=17.80

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/01/07
				Checked	Lizzy	06/01/07
				Drawn	Tina	06/01/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMC3-XX-XX-XX-WWT3**

Description: SD-IC Socket