



Model No.	POS.1	POS.2	POS.3
1MD1	ON	NONE	ON
Term. Comm.	2-3,5-6		2-1,5-4
SCHEMATIC	N/A		

SWITCH FUNCTION

SPECIFICATIONS

Mechanical Life:	40,000 make-and-break cycles	Case:	Dially Phthalate, UL94V-0	R:	0.4 Volt-Amps (VA) max. @20V max. (AC or DC)
Contact Resistance:	10mΩ max. initial @ 2-4 VDC	Actuator:	Brass, Chrome Plated	Q:	2Amps @250VAC
	100mA for both silver and gold contacts	Bushing:	Brass, Nickel Plated		5Amps @120 VAC or 28 VDC
Insulation Resistance:	1000MΩ min.	Housing:	Stainless Steel		
Withstanding:	1000 VRMS @ Sea Level	Terminal Contact:	Silver or Gold Plated		
Operating Temp:	-30C to 85C				

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/9/13
				Checked	Lizzy	07/9/13
				Drawn	Tina	07/9/13
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **SWT-1MD1T2B3M2QES-5**

Description: Miniature Toggle Switches