



PCB Layout (B)

SPECIFICATIONS

Current Rating:	1 Amp
Contact Material:	Phosphor Bronze Gold Plating
Contact Resistance:	35mΩ max.
Housing Material:	Thermoplastic UL94V-0, Black
Insulation Resistance:	>500MΩ Min
Front Shell:	Steel Nickel Plated over Copper
Withstanding:	500V AC
Operating Temp:	-55°C ~ +105°C

RoHS compliant

Series	No. of Contacts	Gender	Contact Plating	PCB Layout
CMDD	XX	X	SGXX	X
1.27mm SCSI header	26, 36, 40, 50, 68, 100	M=Male F=Female	SG5=5μ" gold SG15=15μ" gold SG30=30μ" gold	S=Standard R=Reverse

Rev.	Description	Date	Approved	Drawing	Name	Date
A	PNT	5/6/08	Greg	Approved	Howard	04/02/07
				Checked	Lizzy	04/02/07
				Drawn	Tina	04/02/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMDD-100-M-SGXX-S**

Description: 1.27mm Pin Type 100P Plug Headers Vertical Mount