



**SPECIFICATIONS**

Contact Resistance: 30m Ohm Max.  
 Insulation Resistance: 100M Ohm Min. AT 500V DC  
 Voltage Rating & Current: DC12V.2A Max ; AC 100V.1A Max  
 Withstanding: 250V AC for 1 Minute  
 Durability: 100 Cycles  
 Insertion Force: 4.0KG Max.  
 Extraction Force: 0.9KG Min.



Item	Name	Material	Finish
1	Housing	PBT GF	Black
2	Contact	Phos. Bronze T:0.2	Gold:1~3u" ; Ni:40~60u" ; Tin:120u"
3	Shield	Brass T:0.3	Tin Plated Sn: 120-200u"
4	Bottom Cover	PBZT GF	Black

Series	Positions	Type	Plating	Options
CMDJ	XX	X	XX	XX
Circular mini DIN jack	3-8	A=No shield B=Four side shield C=Five side shield	[blank]=Silver SGXX=Selective gold GDXX=Gold XX=Flash if blank; 3, 5, 10, 15, 20, 30µ"	[blank]=DIP FF= Ferrite filter SM=Surface mount L=Latch KT=Kinked tail PG=Panel grounds SL= Slim

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/04/10
				Checked	Lizzy	08/04/10
				Drawn	Tina	08/04/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMDJ-03-C**

Description: Mini DIN Jack Flat 3 Pin DIP