



Code	Color
K	Black
N	Brown
R	Red
O	Orange
L	Yellow
G	Green
B	Blue
V	Violet
Y	Gray
W	White

SPECIFICATIONS

Contact Carrying Capacity: AC 100V 1A Max.
 DC 12V 2A Max.
 Contact Resistance: 30 mohm max.
 Insulation Resistance: 50 mohm min at dc 250V
 Voltage Withstanding: AC 250V for 1 minute
 Insertion Force: 1.0—4.5kg
 Withdrawal Force: 0.8—3.0kg

Item	Name	Material	Finish
1	Body	PBT, UL94V-0	
3	Earth Terminal	BSR-H 0.4t	Tin

ARRANGEMENT OF CONTACTS						
NO OF CONTACTS	3	4	5	6	7	8

Series	Type	Positions	Wire Length (mm)	Wire Color
CMDJ	U17	XX	XXX	XXX
Mini DIN Jack	Wired Panel Mount	03-18	Customer Specified	Select codes from chart. List in pin order

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/05/06
				Checked	Lizzy	10/05/06
				Drawn	Tina	10/05/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMDJ-U17-XX-XXX-XXX**

Description: 8P Mini DIN Jack w/ wire Leads