


**SPECIFICATIONS**

Voltage rating: 100 VAC @ 1 amp; 12 VDC @ 2 amps  
 Contact material: Brass  
 Contact plating: Gold  
 Housing material: Nylon66 glass filled  
 Insulation resistance: 50 megohms min. at 500 VAC/1 min.  
 Withstanding: 500 VAC/1 min.  
 Cover material: PE + 2L  
 Shell material: ABS  
 Shield material: Brass  
 Shield plating: Nickel

Series	Contacts	Inlet Diameter
CMDP	XX	X
Mini DIN Plug	03-08	Blank=5.0mm A=6.0mm B=7.0mm

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
A	DWG, PNT, SPEC	4/09/09	Greg	Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'



UNIT: mm

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMDP-XX-X**

Description: Mini DIN plug, assembly type