


Y	AWG
A	22
B	24
C	26
D	28



SPECIFICATIONS

Material: Nylon UL94V-0, Natural
 Contact Material: Phosphor Bronze
 Current Rating: 2A, AC/DC
 Voltage Rating: 250V, AC/DC
 AWG: AWG 28-22
 2-30 circuits

Dimensions					
Circuits (XX)	A	B	Circuits (XX)	A	B
2	2.54	7.62	17	40.64	45.72
3	5.08	10.16	18	43.18	48.26
4	7.62	12.70	19	45.72	50.80
5	10.16	15.24	20	48.26	53.34
6	12.70	17.78	21	50.80	55.88
7	15.24	20.32	22	50.80	58.42
8	17.78	22.86	23	55.88	60.96
9	20.32	25.40	24	58.42	63.50
10	22.86	27.94	25	60.96	66.04
11	25.40	30.48	26	63.50	68.58
12	27.94	33.02	27	66.04	71.12
13	30.48	35.56	28	68.58	73.66
14	33.02	38.10	29	71.12	76.20
15	35.56	40.64	30	73.66	78.74
16	38.10	43.18			

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/20/09
				Checked	Lizzy	03/20/09
				Drawn	Tina	03/20/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMT-TK-254-2228Y-XX**

Description: 2.54mm Wire To Board