



**SPECIFICATIONS**

Rated: 300V 25A  
 Withstanding: AC2000V/Min  
 Insulation Resistance: 500MΩ/DC500V  
 Wire Range: 22~12AWG  
 Max Torque: 1.2N.m 10.6Lb In  
 Housing: PA66, UL94V-0  
 Terminal: 0.8t, Tin Plated  
 Screw: Steel, M4 Nickel Plated  
 No. Of Contacts: 02-15  
 Temperature Range: -40C ~ +105C

Series	Type/Options	Pitch	Positions	Color
CMTB	1165XYZ	1100	XX	BK
Terminal block	X: Blank=Straight center pin S=Straight side pin R=Right angle H=Center solder tab pin Y:F=Mounting flange Z:C=Cover	762=7.62mm 825=8.25mm 850=8.50mm 1000=10.00mm 1100=11.00mm	02-15	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/04/07
				Checked	Lizzy	06/04/07
				Drawn	Tina	06/04/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-1165XYZ-1100-XX-BK**

Description: 11.00mm Pitch Barrier Strip