



N=Number of contacts



SPECIFICATIONS

- Voltage rating: 300 VAC
- Current rating: 8 amps
- Terminal body: Machined brass
- Contact resistance: 20 milliohms max.
- Housing material: Polyamide, glass filled, UL94V-0
- Insulation resistance: 5,000 megohms min.
- Wire guard: Phosphor bronze, tin plated
- Screws: Steel, zinc or tin plated
- Withstanding: 1500 VAC/1-min.
- Wire range: 16-26AWG
- Operating temp.: -33°C to +120°C

Series	Type	Pitch	Positions	Color
CMTB	201011	XXX	XX	XX
Terminal block	Short body	500, 508, 1000, 1016	2-6	GN=Green BK=Black BL=Blue GY=Gray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-201011-508-XX-XX**

Description: Short body terminal block plug