

SECTION A-A

Dimensions					
Poles	L1	L2	Poles	L1	L2
2	5.00	11.40	13	60.00	66.40
3	10.00	16.40	14	65.00	71.40
4	15.00	21.40	15	70.00	76.40
5	20.00	26.40	16	75.00	81.40
6	25.00	31.40	17	80.00	86.40
7	30.00	36.40	18	85.00	91.40
8	35.00	41.40	19	90.00	96.40
9	40.00	46.40	20	95.00	101.40
10	45.00	51.40	21	100.00	106.40
11	50.00	56.40	22	105.00	111.40
12	55.00	61.40	23	110.00	116.40
			24	115.00	121.40

SPECIFICATIONS
 Pin Header: Brass, Tin Plated
 Housing: PA66, UL94V-0
 Rated Voltage: 300V
 Rated Current: 15A
 Contact Resistance: 20mΩ
 Insulation Resistance: 5000MΩ/1000V
 Withstanding: AC1500V/1Min
 Temp Range: 040C to +105C
 Max Soldering: +250C for 5 Sec.

Series	Type	Pitch	Poles	Color
CMTB	2EDGCV	500	XX	XX
Terminal Block	2EDGCV Type	500=5mm 508=5.08mm 750=7.5mm 762=7.62mm	02-24	BK=Black GN=Green (std) BL=Blue RD=Red OR=Orange WT=White GY=Gray



RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/05/06
				Checked	Lizzy	10/05/06
				Drawn	Tina	10/05/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-2EDGCV-500-XX-XX**

Description: Pluggable Terminal Blocks, Closed End



Angles ± 3'

UNIT: mm