



N: Number of contacts
A: Pitch

SPECIFICATIONS

Contact Material: Brass, Tin Plated
Housing Material: PA66, UL94V-0
Rated Voltage: 300V
Current Rating: 15A
Contact Resistance: 20mΩ
Insulation Resistance: 5000MΩ/1000V
Withstanding: AC1500V/1Min
Wire Range: 28-12AWG 2.5mm
Strip Length: 5-6mm
Temperature Range: -40°C ~ +105°C
Max Soldering: P +250°C for 5 Sec.

Series	Type	Pitch	Positions	Color
CMTB	8891	XXX	XX	XQ
Terminal block	Screwless 45° entry	500=5.00mm 508=5.08mm (.200") 750=7.5mm 762=7.62mm 1000=10.0mm 1016=10.16mm	02-15	B=Blue W=White Q=Qty

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/10/14
				Checked	Lizzy	10/10/14
				Drawn	Tina	10/10/14
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-8891-500-10-WB8W**

Description: Screwless terminal block