


N: Number of contacts
A=Pitch



SPECIFICATIONS

Contact Material: Brass, Tin Plated
 Housing Material: PA66, UL94V-0
 Rated Voltage: 300V
 Current Rating: 15A
 Contact Resistance: 20mΩ
 Insulation Resistance: 5000MΩ/1000V
 Withstanding: AC1500V/1Min
 Wire Range: 28-12AWG 2.5mm
 Strip Length: 5-6mm
 Temperature Range: -40°C ~ +105°C
 Max Soldering:P +250°C for 5 Sec.

Series	Type	Pitch	Positions	Color
CMTB	8891	XXX	XX	XX
Terminal block	Screwless 45° entry	500=5.00mm	02-15	GN=Green BK=Black
		508=5.08mm (.200")		
		750=7.5mm		
		762=7.62mm		
		1000=10.0mm		
1016=10.16mm				

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-8891-500-XX-XX**

Description: Screwless terminal block