



**SPECIFICATIONS**  
 Contact Material: Brass, Tin Plated  
 Housing Material: PA66, UL94V-0  
 Rated Voltage: 300V  
 Current Rating: 15A  
 Contact Resistance: 20mΩ  
 Insulation Resistance: 5000MΩ/1000V  
 Withstanding: AC1500V/1Min  
 Wire Range: 28-12AWG 2.5mm  
 Strip Length: 5-6mm  
 Temperature Range: -40°C ~ +105°C  
 Max Soldering:P +250°C for 5 Sec.

Series	Type	Pitch	Positions	Color
CMTB	8898	XXX	XX	XX
Terminal block	Screwless 45° entry	500=5.00mm	02-15	GN=Green BK=Black
		508=5.08mm (.200")		
		750=7.5mm		
		762=7.62mm		
		1000=10.0mm		
1016=10.16mm				

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-8898-500-XX-XX**

Description: Screwless terminal block