


N:NUMBER OF CONTACTS



RECOMMEND PCB LAYOUT(TOLERANCE=±0.05)

SPECIFICATIONS

- Voltage Rating: 300V
- Current Rating: 8A
- Contact Resistance: 20mΩ
- Insulation Resistance: 5000MΩ / 1000V
- Withstanding: AC 2000V / 1Min
- Pin Header: Brass, Tin Plated
- Housing: PA66, UL94V-0
- Max Soldering: +250°C for 5 Sec
- Temp Range: -40°C to +130°C

Series	Type	Pitch	Positions	Plating	Color
CMTB	F040	XXX	XX	XX	XX
Pluggable Terminal block	Vertical header	350=3.50mm 381=3.81mm See also 500=5.00mm 508=5.08mm (.200") 750=7.50mm 762=7.62mm	02-24	TN=Tin	GN=Green BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/08/07
				Checked	Lizzy	07/08/07
				Drawn	Tina	07/08/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F040-381-XX-GN**

Description: Pluggable terminal block, vertical PCB mount