



SPECIFICATIONS
 Voltage Rating: 300V (UL), 250V (VDE)
 Current Rating: 10A (UL), 18A (VDE)
 Screws: M2.5 Steel Zinc Plated
 Contact: Brass
 Pin Header: Brass, Tin Plated
 Housing: PA66, UL94V-0
 Contact Resistance: 20mΩ
 Insulation Resistance: 5000MΩ/1000V
 Withstanding Voltage: AC1500V/1Min
 Wire Range: 24-12AWG 2.5mm²
 Temp Range: -40C to 105C
 Max Soldering: +250C for 5 sec.
 Torque: 0.4Nm (3.6LB In)
 Strip Length: 6-7mm

Series	Type	Pitch	Positions	Color
CMTB	F128MVA	XXX	XX	XX
Terminal block	Modular Terminal Block	500=5.00mm 508=5.08mm (.200")	02-03	GN=Green BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/02/06
				Checked	Lizzy	06/02/06
				Drawn	Tina	06/02/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F128MVA-508-XX-XX**

Description: Modular Terminal Block