


SPECIFICATIONS

Voltage Rating: 320V
 Current Rating: 9A
 Pin Header: Brass, Tin Plating
 Housing: PBTUL94V-0
 Contact Resistance: 20mΩ
 Insulation Resistance: 5000M Ω / 1000V
 Withstanding: AC 1500V / 1 Min
 Wire Range: 0.2-2AWG 0.75mm²
 Max Soldering: +250C, for 5 Sec.
 Strip Length: 7mm
 Package: Tape & Reel
 Temp Range: -40C to +105C



P. C. B. LAYOUT

Series	Type	Pitch	Positions	Color
CMTB	F151	400	XX	XX
Terminal block	Side entry, PCB SMTmount	400=4.00mm	01-03	GY=Gray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/05/12
				Checked	Lizzy	10/05/12
				Drawn	Tina	10/05/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F151-400-03-GY**

Description: Terminal block, side entry surface mount,

