



SPECIFICATIONS

Screws: M2.5 Steel Zinc Plated
 Wire Guard: Phosphor Bronze Ni Plated
 Housing: PA66, UL94V-0
 Voltage Rating: 300V
 Current Rating: 10A
 Contact Resistance: 20mΩ
 Insulation Resistance: 5000MΩ/1000V
 Withstanding Voltage: AC1500V/1Min
 Wire Range: 28-16AWG 1.5mm²
 Temp Range: -40C ~ +105C
 Max Soldering: +250C for 5 Sec.
 Torque: 0.4Nm(3.6lB. IN)
 Strip Length: 4.5-5mm

Series	Type	Pitch	Positions	Color
CMTB	F331	XXX	XX	XX
Terminal block	F331 Type	500, 508, 1000, 1016	02,03,08, 16	GN=Green BK=Black GY=Gray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/04/08
				Checked	Lizzy	08/04/08
				Drawn	Tina	08/04/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		


Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F331-500-XX-XX**

Description: Euro Terminal Blocks Pitch 5.0mm